

MODEL NUMBER	NOM. HP	VOLTAGE PH.	NOMINAL BTU	RLA	LRA	FAN QTY	FLA	TOTAL MCA	MFA	SUCTION LINE	LIQUID LINE	UNIT WT
LOW TEMPERATURE -40 - +10 (R404, R507)												
CCHA0-0075-B404	0.75	115/1	3550	6	39	1	0.65	8.2	15/	5/8	3/8	100
CCHA0-0100-B404	1	230/1	4370	8	42	1	0.7	10.7	15/	5/8*	3/8*	105
CCHA0-0150-B404	1.5	230/1	6280	9.6	55	1	0.85	12.9	20	7/8*	3/8*	125
CCHA0-0200-B404	2	230/1	10030	13.8	65	1	0.85	18.1	30	7/8*	3/8*	135
CCHA0-0200-B404	2	230/3	10030	5.1	30	1	0.44	6.8	15	7/8*	3/8*	135
CCHA0-0200-B404	2	460/3	10030	13.8	65	1	0.85	18.1	30	7/8*	3/8*	135
CCHA0-0300-B404	3	230/1	15040	20.5	110	2	0.85	27.3	45	7/8*	3/8*	210
CCHA0-0300-B404	3	230/3	15040	11.5	78	2	0.85	16.1	25	7/8*	3/8*	210
CCHA0-0300-B404	3	460/3	15040	5.8	39	2	0.44	8.1	15	7/8*	3/8*	210
CCHA0-0400-B404	4	230/1	20060	25.1	135	2	0.85	34.2	60	7/8*	3/8*	250
CCHA0-0400-B404	4	230/3	20060	10.5	60	2	0.85	14.3	30	7/8*	3/8*	250
CCHA0-0400-B404	4	460/3	20060	25.1	135	2	0.44	34.2	60	7/8*	3/8*	250
CCHA0-0600-B404	6	230/1	30080	40.1	175	2	0.85	45.8	75	7/8*	1/2*	400
CCHA0-0600-B404	6	230/3	30080	23.2	145	2	0.85	32.2	50	7/8*	1/2*	400
CCHA0-0600-B404	6	460/3	30080	11.4	78	2	0.44	16.2	30	7/8*	1/2*	400
MEDIUM/HIGH TEMPERATURE +10 - +35 (R22)												
CCHA0-0075-B22	0.75	115/1	9720	10.5	61	1	0.89	14	20	5/8*	3/8*	100
CCHA0-0100-B22	1	230/1	12280	8.6	40	1	0.7	11.5	20	5/8*	3/8*	110
CCHA0-0150-B22	1.5	230/1	18310	9.8	45	1	0.85	13.1	20	5/8*	3/8*	130
CCHA0-0150-B22	1.5	230/3	18310	6.4	48	1	0.89	8.9	15	5/8*	3/8*	130
CCHA0-0200-B22	2	230/1	23800	12	57	2	0.85	16.7	25	7/8*	3/8*	205
CCHA0-0200-B22	2	230/3	23800	7.7	48	2	0.85	11.3	15	7/8*	3/8*	205
CCHA0-0200-B22	2	460/3	23800	3.8	24	2	0.44	8.4	15	7/8*	3/8*	205
CCHA0-0300-B22	3	230/1	36970	19.2	97	2	0.85	25.7	40	7/8*	1/2*	220
CCHA0-0300-B22	3	230/3	36970	12.8	78	2	0.85	17.7	25	7/8*	1/2*	220
CCHA0-0300-B22	3	460/3	36970	6	39	2	0.44	8.4	15	7/8*	1/2*	220
CCHA0-0400-B22	4	230/1	52820	28.8	138	2	1.9	39.8	60	7/8*	1/2*	300
CCHA0-0400-B22	4	230/3	52820	15.4	106	2	1.9	23.1	35	7/8*	1/2*	300
CCHA0-0400-B22	4	460/3	52820	7.5	53	1	1.9*	12.2	15	7/8*	3/8*	300
CCHA0-0500-B22	5	230/1	60330	30.1	170	1	1.9	41.4	70	7/8*	1/2*	350
CCHA0-0500-B22	5	230/3	60330	20.5	124	1	1.9	29.4	45	7/8*	1/2*	350
CCHA0-0500-B22	5	460/3	60330	8.8	62	1	1.9	13.8	20	7/8*	1/2*	350
CCHA0-0600-B22	6	230/3	72150	25.8	198	1	2.7	34.6	60	7/8*	1/2*	450
CCHA0-0600-B22	6	460/3	72150	13.6	102	1	1.9	18.5	30	7/8*	1/2*	450
CCHA0-0750-B22	7.5	230/3	93550	27.1	226	1	5.4	39.1	60	1 1/8*	5/8*	525
CCHA0-0750-B22	7.5	460/3	93550	14.8	112	1	3.9	23.5	35	1 1/8*	5/8*	525
CCHA0-1000-B22	10	230/3	120000	47.2	34.8	1	5.4	64.9	90	1 1/8*	5/8*	600
CCHA0-1000-B22	10	460/3	120000	22.6	160	1	3.9	32	50	1 1/8*	5/8*	600
CCHA0-1500-B22	15	230/3	180000	55.4	418	1	5.4	79.3	120	1 3/8*	7/8*	750
CCHA0-1500-B22	15	460/3	180000	30.1	224	1	3.9	47	75	1 3/8*	7/8*	750